

Page: 1

Compilation date: 05/05/2015

Revision No: 08

Section 1: Identification of the substance/mixture and of the company/undertaking

CLEANTRAY

1.1. Product identifier

Product name: CLEANTRAY

Product code: AF7758

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaning of equipment by immersion.

1.3. Details of the supplier of the safety data sheet

Company name:	Kilco (International) Ltd
	Broomhouses 2 Industrial Estate
	Old Glasgow Road
	Lockerbie
	DG11 2SD
	United Kingdom
Tel:	+44 (0) 157 620 5480
Email:	sds@kilco.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 207 858 1228

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: C: R35

Classification under CLP: Skin Corr. 1A: H314

Most important adverse effects: Causes severe burns.

2.2. Label elements

Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion



Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting. P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

CLEANTRAY

Page: 2

Rinse skin with water/shower.

P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Label elements under CHIP:

Hazard symbols: Corrosive.



Risk phrases:R35: Causes severe burns.Safety phrases:S26: In case of contact with eyes, rinse immediately with plenty of water and seek
medical advice.S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.S45: In case of accident or if you feel unwell, seek medical advice immediately (show
the label where possible).

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM SILICATE

E	EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-	-687-4	1344-09-8	Xi: R38; Xi: R41	Eye Dam. 1: H318; Skin Irrit. 2: H315	10-30%

POTASSIUM HYDROXIDE

215-181-3	1310-58-3	Xn: R22; C: R35	Acute Tox. 4: H302; Skin Corr. 1A:	1-10%
			H314	

TETRAPOTASSIUM PYROPHOSPHATE

	230-785-7	7320-34-5	Xi: R36	Eye Irrit. 2: H319	1-10%	
--	-----------	-----------	---------	--------------------	-------	--

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Transfer to hospital if there are burns or symptoms of poisoning.

- **Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.
 - Ingestion: Wash out mouth with water. Do not induce vomiting. Give 1 cup of water to drink every 10

CLEANTRAY

	Page:	3
minutes. If unconscious, check for breathing and apply artificial respiration if necessary.		
If unconscious and breathing is OK, place in the recovery position. Transfer to hospital		
as soon as possible.		
Remove casualty from exposure ensuring one's own safety whilst doing so. If		
unconscious and breathing is OK, place in the recovery position. If conscious, ensure		
the casualty sits or lies down. If breathing becomes bubbly, have the casualty sit and		
provide oxygen if available. Transfer to hospital as soon as possible.		
and effects, both acute and delayed		
Blistering may occur. Progressive ulceration will occur if treatment is not immediate.		

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: Blistering may occur. Progressive ulceration will occur if treatment is not immediate.

Eye contact: Corneal burns may occur. May cause permanent damage.

Inhalation: Remove casualty from exposure ensuring

Ingestion: Corrosive burns may appear around the lips. Blood may be vomited. There may be bleeding from the mouth or nose.

Inhalation: There may be shortness of breath with a burning sensation in the throat. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Corrosive. In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

CLEANTRAY

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Clean-up should be dealt with only by qualified personnel familiar with the specific substance. Absorb into dry earth or sand. Transfer to a closable, labelled salvage

container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): The identified uses for this product are detailed in Section 1.2

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

POTASSIUM HYDROXIDE

Workplace exposure limits:			Respirable dust	
State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Tightly fitting safety goggles. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

CLEANTRAY

				Page:	5
Colour:	Colourless				
Oxidising:	Non-oxidising (by EC criteria)				
Solubility in water:	Soluble				
Flammability limits %: lower:	Not applicable.	upper:	Not applicable.		
Flash point°C:	Not applicable. Re	elative density:	1.25 - 1.3		

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM SILICATE

DERMAL	RAT	LD50	>5000	mg/kg
ORAL	RAT	LD50	3400	mg/kg

POTASSIUM HYDROXIDE

ORL RA		273	mg/kg
--------	--	-----	-------

CLEANTRAY

Relevant effects for mixture:

Effect	Route	Basis
Corrosivity	OPT INH DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	Blistering may occur. Progressive ulceration will occur if treatment is not immediate.
Eye contact:	Corneal burns may occur. May cause permanent damage.
Ingestion:	Corrosive burns may appear around the lips. Blood may be vomited. There may be
	bleeding from the mouth or nose.
Inhalation:	There may be shortness of breath with a burning sensation in the throat. Exposure may
	cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.
Other information:	Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

SODIUM SILICATE

ALGAE	72H ErC50	207	mg/l
Daphnia magna	48H EC50	1700	mg/l
FISH	96H LC50	1108	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

CLEANTRAY

Section 14: Transport information

14.1. UN number

UN number: UN1719

14.2. UN proper shipping name

Shipping name: CAUSTIC ALKALI LIQUID, N.O.S.

(POTASSIUM HYDROXIDE; SODIUM SILICATE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: ||

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 2

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
	This safety data sheet is prepared in accordance with Commission Regulation (EC) No
	1272/2008.
Phrases used in s.2 and s.3:	H302: Harmful if swallowed.
	H314: Causes severe skin burns and eye damage.
	H315: Causes skin irritation.
	H318: Causes serious eye damage.
	H319: Causes serious eye irritation.
	R22: Harmful if swallowed.
	R35: Causes severe burns.

Page: 7

Marine pollutant: No

CLEANTRAY

R36: Irritating to eyes.R38: Irritating to skin.R41: Risk of serious damage to eyes.Legal disclaimer:The above information is believed to be correct but does not purport to be all inclusive
and shall be used only as a guide. This company shall not be held liable for
any damage resulting from handling or from contact with the above product.
Kilco (International) Ltd, Registered Office: 1A Trench Road, Mallusk,
Newtownabbey, Belfast, BT36 4TY. Place of Registration: Northern Ireland,
Registration Number: NI3240

Page: 8